

MARMORAN

SPECIALISTS WALL COATINGS
The Architects' Choice since 1969

STUCCO CRETE

**STUCCO CRETE IS A SOFT INTERNAL FINISH FOR WALLS & CEILINGS,
AVAILABLE IN PASTEL COLOURS.**



PRODUCT INFORMATION

- Stucco Crete is supplied ready mixed for application by spray which is then partially flattened with a roller.
- No on-site mixing machinery or water required.
- Suitable for fast-track projects. Fast application and rapid drying out – reducing the programme time.
- The finish is smooth or textured, depending on application method.
- Textured ceilings do not require any further decoration or painting.
- Can be used as a skim and a top coat
- Décor Crete has inherent flexibility and is less prone to cracking than traditional plaster.
- Virtually all types of surfaces can be coated to a uniform appearance e.g. suitably primed metal, plaster, concrete and composition boards.
- Water based, non-toxic, contains no asbestos fibres or other harmful ingredients. LOW VOC LEVEL
- It is recommended that it is sealed with two coats of glaze.

PRODUCT CODE DEC01

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION

STUCCO CRETE is a ready mixed surfacing compound composed of inert fillers of marble dust, crushed limestone, whiting, sand and other minerals specially graded to give excellent handling and filling capabilities. To this is added a binding medium, a plastic combination, which is age resistant, chemically inert and non-toxic. Fungicides and rust preventatives are also added.

APPLICATION METHOD

Applied by spray and /or trowel. Supplied ready for use.

DO NOT THIN. Clean with water

COLOUR

Pastel shades

MARMORAN

SPECIALISTS WALL COATINGS

The Architects' Choice since 1969

STUCCO CRETE

APPLICATION METHOD

Trowel or spray (using a Marmoran Hopper Gun) depending on the desired finish. The displayed sample panel is applied by spraying on the plaster and then partially flattening with a roller. Apply in one or more coats, with intermittent drying between coats.

USES

- On all types of interior building surfaces such as cement or gypsum plaster, concrete, building boards and old painted surfaces that have been suitably primed.
- As a decorative textured ceiling coating which can then be left without any further decoration or painting.
- Applied as a decorative finish by roller, comb, spray and /or trowel..

PRODUCT DATA	
Thickness per coat	2.0mm WFT Maximum per coat
Solid content	71 % ± 2
VOC LEVELS	8g/L 0.68%
Coverage	1.75KG per m ² / mm/coat.
*Drying Times 25 deg C @ 65% RH	
Surface	2 to 4 hours dependent on humidity and temperature
Hard	16 – 24 hours
Over coating	4 -12hours
Application	24 hours
Clean/ thin	Water by 2 – 5% by volume for spray if required
Flash point – fire rating	None. Class 0 surface spread of flame
Toxicity	Free of toxic matter
Shelf Life and Storage	6 - 8 Months in unopened containers. Store in a cool dry and well-ventilated place away from heat or open flame. Do not allow to freeze.

TRANSPORT

This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)

HANDLING & SAFETY

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER

All information contained herein is given in good faith, based on our specialized knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.